



MARKET FORGE

STERILMATIC STEAM STERILIZERS

The Largest Capacity in the Most Compact Space

Small on the outside, the Sterilmatics has as much inside capacity as many large, more costly conventional sterilizers and up to five times the capacity of smaller table top units.

Economical, reliable and simple to operate, the versatile Sterilmatics provides the highest standards of sterilizing performance in a number of facilities, such as, Laboratories, Veterinary Clinics, Food Processing Plants, Wineries, Fisheries, Dairy Processing Plants, and more.

Sterilize glass beakers, pipettes, test tubes and flasks. Metal and plastic instruments, syringes, needles, brushes, rubber gloves, catheters, rubber tubing, dressings, linens, petri dishes and more.

DIGITAL STERILIZER

Standard Features

- LCD display screen; monitor temperature, time and pressure
- Select temperature in °F (PSI) or °C (kPa)
- Sterilizing temps can range from 225°F (107°C) to 250°F (121°C)
- Choose from fast or slow exhaust
- Built-in data recorder and printer
- Programmable buttons to store up to 3 temp/time/venting cycle parameters
- Maintain a set temperature with a built-in microprocessor
- Electric steam trap
- Removable pan supports
- 18-3/4" wide x 28-5/8" high x 31" deep (56-1/4" high on optional stand)



Digital Steam Sterilizers

MODEL	DESCRIPTION	PART NUMBER	APPROX. SHIPPING Wt LBS/KG	LIST PRICE
STM-ED*	Digital sterilmatic (microprocessor controlled) with programmable time, temperature and venting (230°-250°F / 110°-121°C)	95-6300	150/68	\$15,020
STM-EDX**	Export model digital sterilmatic (microprocessor controlled) with programmable time, temperature and venting (230°-250°F / 110°-121°C)	95-6301	150/68	\$15,680

* These models are available in 208, or 240 Volts, 60Hz, 1 or 3 ph

** Export models are available in 220/380 Volts, 50Hz, 1 or 3 ph 4 wire or 240/415 Volts, 50Hz, 1 or 3 ph 4 wire

Adjustable feet are included as standard in all units.



Shown on optional stand 95-6060



ANALOG STERILIZERS

Standard Features

- Automatic temperature controls
- Temperature up to 250°F (121°C)
- Thermostatic steam trap
- Thermometer range 180°-300°F (82°-149°C)
- 0-30 lb. steam gauge
- 0-60 minute timer
- Low water cut-off, signal light, and safety valve
- Flat perforated steam baffle
- Removable pan supports
- 18-3/4" wide x 27-5/8" high x 31" deep (55-1/4" high on optional stand)



Analog Steam Sterilizers

MODEL	DESCRIPTION	PART NUMBER	APPROX. SHIPPING WT LBS/KG	LIST PRICE
STM-E*	Analog sterilmatic	95-2678	150/68	\$12,510
STM-EL*	Analog sterilmatic with adjustable temperature controls (230°-250°F)	95-3441	150/68	\$12,870
STM-EX**	Export model analog sterilmatic	95-2902	150/68	\$13,250
STM-ELX**	Export model analog sterilmatic with adjustable temperature controls (230°-250°F)	95-2903	150/68	\$13,530

* These models are available in 208, or 240 Volts, 60Hz, 1 or 3 ph

** Export models are available in 220/380 Volts, 50Hz, 1 or 3 ph 4 wire or 240/415 Volts, 50Hz, 1 or 3 ph 4 wire
Adjustable feet are included as standard in all units.

TERMS, CONDITIONS AND ORDERING INFORMATION

Orders are subject to ACCEPTANCE by Market Forge Home Office. ALL PRICES are subject to change without notice. Inspect merchandise immediately on receipt and notify carrier if SHIPMENT IS DAMAGED. All claims must be filed with carrier.

CANCELLED ORDERS and RETURN MERCHANDISE are subject to a restocking charge of 20% on domestic models and 30% on export (50Hz) models. Returned merchandise must be shipped prepaid after obtaining our written return authorization.

QUOTATIONS are subject to acceptance within 90 days. SHIPMENT must be within 6 months from date of order or quotation or may be subject to increase in price. Quotations will be submitted on request for delivery requirements beyond 6 months.

WARRANTY: 90 Days Labor, 1 Year Parts. NO EXTENDED WARRANTY!

FREIGHT CLASSIFICATION: 85

INTERNATIONAL ORDERS: Any orders outside the continental U.S. and Canada will be subject to an 8% Warranty Administration Fee added to the invoice and could be subject to other charges.



OPTIONS & ACCESSORIES

PART NUMBER	DESCRIPTION	APPROX. SHIPPING WT LBS/KG	LIST PRICE
95-6060	Stainless Steel Stand with Adjustable Shelf & Feet - 28" High*	23/10	\$990
95-6054	Extra Shelf (For Stand Listed Above)	4/1.8	\$265
10-1203	12" x 20" x 2-1/2" Perforated Tray (Unit will hold three of this size)	5/2.3	\$240
10-1204	12" x 20" x 4" Perforated Tray (Unit will hold (2) of these, as well as (1) - 2-1/2" tray)	6/2.7	\$275
10-1205	12" x 20" x 6" Perforated Tray (Unit will hold (1) of these, as well as (1) - 2-1/2" tray)	7/3.2	\$410
10-1228	12" x 20" x 2-1/2" - Wire Basket	4/1.8	\$250
10-1229	12" x 20" x 4" - Wire Basket	6/2.7	\$260
95-0436	Exhaust Condenser (Can't be connected to outside vent)	14/6.4	\$1,460
95-3629	Exhaust Condenser 240V, 50/60 Hz (Can be used with "Export" Sterilizers)	14/6.4	\$1,500
95-6061	Spare Parts Kit (STM-E & STM-EL Models)	6/2.7	\$760
95-6062	Spare Parts Kit (STM-EX & STM-ELX Models) Export	6/2.7	\$840
95-6233	Recording Thermometer (Provides Continuous 120 Volts / 60 Hz)	5/2.3	\$2,180
95-6234	Recording Thermometer (Provides Continuous 230 Volts / 50 Hz) Export	5/2.3	\$2,470
10-7933	Replacement 24 Hour Recording Chart (Fahrenheit)	1/.5	\$110
08-6244	Replacement 24 Hour Recording Chart (Celsius) Export	1/.5	\$95

* Sterilmatic overall height with stand is 55-1/4" (1403mm) for analog units and 56-1/4" (1429mm) for digital units



10-1203




10-1228



10-1204



10-1205



10-7933



95-6060 S/S Stand



95-6233



MARKET FORGE

Visit our website for the most up to date literature: www.marketforge.com

PRICES FOR OPTIONS APPLICABLE ONLY WHEN ORDERED WITH EQUIPMENT.

THE COMPANY RESERVES THE RIGHT TO MAKE SUBSTITUTIONS OF COMPONENTS WITHOUT PRIOR NOTICE.

REVISED 01.01.2017



44 LAKESIDE AVENUE
BURLINGTON, VT 05401
1.802.658.6600
FAX 1.802.864.0183